





## DS-S560-2X2



46" - 60"  
(117 - 152 cm)

500 lb  
(227 kg)



## ⚠ WARNING

ENG - This product is designed to be installed on solid concrete. Hardware is included for solid concrete installation. Before installing make sure the supporting surface will support the combined load of the equipment and hardware. Screws must be tightly secured. Do not overtighten screws or damage can occur and product may fail. Never exceed the Maximum Load Capacity. Always use an assistant or mechanical lifting equipment to safely lift and position equipment. This product is intended for indoor use only. Use of this product outdoors could lead to product failure or personal injury. Be careful not to pinch fingers when operating the mount. For support please call customer care at 1-800-865-2112.

### ENG Symbols




ENG **WARNING**



ENG Display center.







ENG Screws must get at least three full turns and fit snug.









ENG Do not overtighten screws.



ENG To properly tighten screws: Tighten until screw head makes contact, then tighten another 1/2 turn. Do not overtighten screws.



### ENG Tools Needed for Assembly.




**ENG** This page intentionally left blank.

Parts List		
Description	Qty	Part #
<b>A</b> pedestal	2	147-T1426
<b>B</b> column	2	146-T1131
<b>C</b> cover	2	145-T1809
<b>D</b> vertical support bracket	4	145-T1806
<b>E</b> left adaptor bracket	4	146-1609
<b>F</b> right adaptor bracket	4	146-1608
<b>G</b> computer cover	1	145-T1930
<b>H</b> computer shelf	1	145-T1931
<b>I</b> dual cross support	2	146-T1905
<b>J</b> cord bracket	4	146-T1321
<b>K</b> knob	4	560-1160
<b>L</b> M8 x 16mm socket button screw	40	520-9527
<b>M</b> M8 square nut	16	530-1066
<b>N</b> cover clip	8	590-0317
<b>O</b> M5 x 10mm type-f, socket pin screw	10	520-1164
<b>P</b> 1/4" power bit	1	560-0263
<b>Q</b> 5mm allen wrench	1	560-9640
<b>R</b> nylon shoulder washer	16	590-2233
<b>S</b> M6 x 12mm socket pin screw	16	520-1050
<b>T</b> 4mm allen wrench	1	560-9646
<b>U</b> M6 x 35mm screw	8	520-0717
<b>V</b> rawl bolt #6913	8	5M9-381-H03


**A (2)**

pedestal




**C (2)**

cover



**D (4)**

vertical support  
bracket




**E (4)**

left adaptor  
bracket




**F (4)**













right adaptor  
bracket



**B (2)**



column









**1**

**x2**






## 2-1


x4



## 2-2




 **TIGHTEN  
CONNECTING  
HARDWARE**





3-1

x2



3-2

x2




TOP VIEW





**⚠ WARNING**

ENG - When installing Peerless mounts on a concrete floor, the floor must be at least 8" thick with a minimum compressive strength of 2000 psi. Never attach concrete expansion anchors to concrete covered with plaster, drywall, or other finishing material.

## 4-1





**ENG** Align base. Mark mounting holes.




## 4-2



**ENG** Drill mounting holes into supporting surface (3" (76mm) minimum depth required).






## 4-3






**ENG** Align base. Install using concrete anchors provided.





[ENG] Cross supports must center on columns.

 TIGHTEN  
CONNECTING  
HARDWARE




**ENG** Cross supports must center on columns.

## 6-1


x4

**ENG** Center adaptor brackets vertically on back of screen.





## 6-2

x4




## 7-1

**ENG** Must hang displays on bottom row first;  
Secure pin in "locked" position.








## 7-2




**ENG** Optional: Insert M5 x 10mm type-F socket pin screws  
(O) to lock latches.



**x8**












10-1



10-2



ENG Route cables through cord brackets.



## LIMITED FIVE-YEAR WARRANTY

Peerless Industries, Inc. ("Peerless-AV") warrants to original end-users that each Peerless-AV® mounting product will be free from defects in material and workmanship, under normal use, for the applicable warranty period (from date of the original installation of the product). At its option, Peerless-AV will repair or replace, or refund the purchase price of, any product which fails to conform with this warranty.

**Any implied warranty of merchantability or fitness for a particular purpose shall be limited to the period of the express warranty set forth below.**

**In no event shall Peerless-AV be liable for incidental or consequential damages, whether or not secured by a security device which may be included with the product.**

Some states do not allow limitations on how long an implied warranty lasts, or the exclusion of incidental or consequential damages, so the above limitation and/or the above exclusion may not apply to you.

This warranty does not cover damage caused by incorrect selection, installation or the failure to follow Peerless-AV instructions or warnings when installing, using or storing the product.

This warranty gives specific legal rights, and you may also have other rights which vary from state to state. To make a warranty claim in North America, contact Peerless-AV customer care at 1-800-865-2112. See complete global warranty information for regions outside North America at [www.peerless-av.com/en-uk/customer-care/warranties-returns](http://www.peerless-av.com/en-uk/customer-care/warranties-returns).

**Peerless-AV**

2300 White Oak Circle  
Aurora, IL 60502  
Email: [tech@peerlessmounts.com](mailto:tech@peerlessmounts.com)  
Ph: (800) 865-2112  
Fax: (800) 359-6500  
[www.peerless-av.com](http://www.peerless-av.com)

© 2020, Peerless Industries, Inc.

**Peerless-AV Europe**

Unit 3 Watford Interchange,  
Colonial Way, Watford, Herts,  
WD24 4WP, United Kingdom  
Customer Care  
44 (0) 1923 200 100  
[www.peerless-av.com](http://www.peerless-av.com)

© 2020, Peerless Industries, Inc.

**Peerless-AV América Latina**

Av. de las Industrias 413  
Parque Industrial Escobedo  
General Escobedo N.L., México 66062  
Servicio al Cliente  
01-800-849-65-77  
[www.peerless-av.com](http://www.peerless-av.com)

© 2020, Peerless Industries, Inc.