

DIGITUS Professional mini GBIC (SFP) Module, 1.25 Gbps, 20km, with DDM Feature

4016032391562
DN-81003-01



1.25 Gbps BiDi WDM SFP Module, Up to 20km with DDM support, Singlemode, LC Simplex Connector 1000Base-LX, Tx1310nm/Rx1550nm

The plug and play fiber connection

The DIGITUS® mini GBIC (SFP) transceiver modules offer highest quality and reliability. Whether from switch to switch, converter to switch, converter to converter or any else application: The wide product range of DIGITUS® modules makes possible a flexible usage of the fiber technology. The conformity to the MSA (Multi Source Agreement) standard ensures a compatibility to third party manufacturers.

- | Mini GBIC SFP (Small Form Factor Pluggable) module
- | Supports DDM (Digital Diagnostic Monitoring)
- | Compatible with the following manufacturers: Allied Telesis, Allnet, CISCO, Dell, D-Link, Edimax, Hirschmann, Huawei, Intellinet, KTI Networks, Level One, Linksys, Netgear, PLANET, Tenda, TP-Link, TRENDnet, ZyXEL, ZTE
- | Bidirectional WDM Module - Only one fiber is needed
- | High quality and excellent reliability
- | 1.25 Gbps Maximum Data Rate
- | Compliant to IEEE 802.3z Gigabit Standard
- | Class 1 laser product compliant with EN 60825-1
- | Easy plug-and-play installation
- | MSA (Multi Source Agreement) compliant
- | Hot pluggable
- | Connector: 1x LC Simplex
- | Wavelength: Tx 1310nm / Rx 1550nm
- | Transmission Power: Minimum -5 dBm, Maximum 0 dBm
- | Sensitivity receiving power: minimum -24 dBm
- | For a Distance of up to 20km
- | Suitable for OM3/OM4 Singlemode Fiber Cables
- | Safe fast-locking mechanism
- | 3.3V power supply

Package Content

- | SFP module



Product Number	Form Factor	Speed	Distance	Connector	Wavelength	Operating Temperature	RoHS Status
4016032391562	Mini GBIC	1.25 Gbps	20 km	LC Simplex	1310nm/1550nm	-40 °C to 85 °C	✓
4016032391563	Mini GBIC	1.25 Gbps	20 km	LC Simplex	1310nm/1550nm	-40 °C to 85 °C	✓
4016032391564	Mini GBIC	1.25 Gbps	20 km	LC Simplex	1310nm/1550nm	-40 °C to 85 °C	✓
4016032391565	Mini GBIC	1.25 Gbps	20 km	LC Simplex	1310nm/1550nm	-40 °C to 85 °C	✓
4016032391566	Mini GBIC	1.25 Gbps	20 km	LC Simplex	1310nm/1550nm	-40 °C to 85 °C	✓
4016032391567	Mini GBIC	1.25 Gbps	20 km	LC Simplex	1310nm/1550nm	-40 °C to 85 °C	✓
4016032391568	Mini GBIC	1.25 Gbps	20 km	LC Simplex	1310nm/1550nm	-40 °C to 85 °C	✓
4016032391569	Mini GBIC	1.25 Gbps	20 km	LC Simplex	1310nm/1550nm	-40 °C to 85 °C	✓
4016032391570	Mini GBIC	1.25 Gbps	20 km	LC Simplex	1310nm/1550nm	-40 °C to 85 °C	✓
4016032391571	Mini GBIC	1.25 Gbps	20 km	LC Simplex	1310nm/1550nm	-40 °C to 85 °C	✓
4016032391572	Mini GBIC	1.25 Gbps	20 km	LC Simplex	1310nm/1550nm	-40 °C to 85 °C	✓
4016032391573	Mini GBIC	1.25 Gbps	20 km	LC Simplex	1310nm/1550nm	-40 °C to 85 °C	✓
4016032391574	Mini GBIC	1.25 Gbps	20 km	LC Simplex	1310nm/1550nm	-40 °C to 85 °C	✓
4016032391575	Mini GBIC	1.25 Gbps	20 km	LC Simplex	1310nm/1550nm	-40 °C to 85 °C	✓
4016032391576	Mini GBIC	1.25 Gbps	20 km	LC Simplex	1310nm/1550nm	-40 °C to 85 °C	✓
4016032391577	Mini GBIC	1.25 Gbps	20 km	LC Simplex	1310nm/1550nm	-40 °C to 85 °C	✓
4016032391578	Mini GBIC	1.25 Gbps	20 km	LC Simplex	1310nm/1550nm	-40 °C to 85 °C	✓
4016032391579	Mini GBIC	1.25 Gbps	20 km	LC Simplex	1310nm/1550nm	-40 °C to 85 °C	✓
4016032391580	Mini GBIC	1.25 Gbps	20 km	LC Simplex	1310nm/1550nm	-40 °C to 85 °C	✓
4016032391581	Mini GBIC	1.25 Gbps	20 km	LC Simplex	1310nm/1550nm	-40 °C to 85 °C	✓
4016032391582	Mini GBIC	1.25 Gbps	20 km	LC Simplex	1310nm/1550nm	-40 °C to 85 °C	✓
4016032391583	Mini GBIC	1.25 Gbps	20 km	LC Simplex	1310nm/1550nm	-40 °C to 85 °C	✓
4016032391584	Mini GBIC	1.25 Gbps	20 km	LC Simplex	1310nm/1550nm	-40 °C to 85 °C	✓
4016032391585	Mini GBIC	1.25 Gbps	20 km	LC Simplex	1310nm/1550nm	-40 °C to 85 °C	✓
4016032391586	Mini GBIC	1.25 Gbps	20 km	LC Simplex	1310nm/1550nm	-40 °C to 85 °C	✓
4016032391587	Mini GBIC	1.25 Gbps	20 km	LC Simplex	1310nm/1550nm	-40 °C to 85 °C	✓
4016032391588	Mini GBIC	1.25 Gbps	20 km	LC Simplex	1310nm/1550nm	-40 °C to 85 °C	✓
4016032391589	Mini GBIC	1.25 Gbps	20 km	LC Simplex	1310nm/1550nm	-40 °C to 85 °C	✓
4016032391590	Mini GBIC	1.25 Gbps	20 km	LC Simplex	1310nm/1550nm	-40 °C to 85 °C	✓
4016032391591	Mini GBIC	1.25 Gbps	20 km	LC Simplex	1310nm/1550nm	-40 °C to 85 °C	✓
4016032391592	Mini GBIC	1.25 Gbps	20 km	LC Simplex	1310nm/1550nm	-40 °C to 85 °C	✓
4016032391593	Mini GBIC	1.25 Gbps	20 km	LC Simplex	1310nm/1550nm	-40 °C to 85 °C	✓
4016032391594	Mini GBIC	1.25 Gbps	20 km	LC Simplex	1310nm/1550nm	-40 °C to 85 °C	✓
4016032391595	Mini GBIC	1.25 Gbps	20 km	LC Simplex	1310nm/1550nm	-40 °C to 85 °C	✓
4016032391596	Mini GBIC	1.25 Gbps	20 km	LC Simplex	1310nm/1550nm	-40 °C to 85 °C	✓
4016032391597	Mini GBIC	1.25 Gbps	20 km	LC Simplex	1310nm/1550nm	-40 °C to 85 °C	✓
4016032391598	Mini GBIC	1.25 Gbps	20 km	LC Simplex	1310nm/1550nm	-40 °C to 85 °C	✓
4016032391599	Mini GBIC	1.25 Gbps	20 km	LC Simplex	1310nm/1550nm	-40 °C to 85 °C	✓
4016032391600	Mini GBIC	1.25 Gbps	20 km	LC Simplex	1310nm/1550nm	-40 °C to 85 °C	✓

DIGITUS Professional mini GBIC (SFP) Module, 1.25 Gbps, 20km, with DDM Feature

4016032391562

DN-81003-01

→ Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	0,06	12,00	9,00	3,00	324,00
Packaging Unit Inside	1	0,06	12,00	9,00	3,00	324,00
Packaging Unit Single	1	0,06	12,00	9,00	3,00	324,00
Net single without Packaging	1	0,00	0,00	0,00	0,00	0,00