

# DIGITUS Aluminum Outlet Strip, 6 safety outlets with circuit breaker

DN-95417  
EAN 4016032456636



**DIGITUS 1U Aluminum PDU, rackmountable 6x safety outlet, 16A, 4000W, 250VAC 50/60Hz,**

**Safety, order and flexibility in the server rack - the DIGITUS® 482.6 mm (19") socket strips.**

- 6 child safety outlets 250VAC 50/60Hz / 16A / 4000W
- Circuit Breaker: 16 A, Type-C
- Circuit breaker: Short-circuit breaking capacity (I<sub>cn</sub> & I<sub>cs</sub>) - 6000A
- 45° arranged sockets: No blocking or obscuring of adjacent sockets
- Mounting bracket for 482.6 mm (19") mounting
- Mounting brackets are variably fixed in 8 positions, 90° and 45° in 4 directions
- High quality aluminum casing

- Child safety device: Plastic covers close the contacts on the socket
- Input voltage: 230 V/AC
- Frequency: 50 ~ 60 Hz
- Mains supply line with earthing contact plug: 1.8 m, 3G x 1.5 mm<sup>2</sup>
- Measurements: L 48,1 x B 4,5 x H 8,3 cm
- Weight: 800 g
- Color: silver/black

**Package contents**

- 1 x 482.6 mm (19") Aluminum 6-Outlet Socket Strip, 1 U with Circuit Breaker
- 2 x 482.6 mm (19") variable mounting brackets
- 1x user manual

**Logistics**

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	10	8.00	48.00	37.00	32.00	56,832.00
Packaging Unit Inside	1	0.80	12.00	65.00	5.80	4,524.00
Packaging Unit Single	1	0.80	78.00	12.00	8.50	7,956.00
Net single without Packaging	1	0.62	78.00	12.00	8.50	7,956.00

**More images:**



